

L Number	Hits	Search Text	DB	Time stamp
1	294	mounting with component and mounting with head and (recogni\$4 camera) with (nozzle suction)	USPAT; EPO; JPO	2004/05/28 12:11
2	158	(mounting with component and mounting with head and (recogni\$4 camera) with (nozzle suction)) and 29/\$.ccls.	USPAT; EPO; JPO	2004/05/28 11:50
3	97	((mounting with component and mounting with head and (recogni\$4 camera) with (nozzle suction)) and 29/\$.ccls.) and rotating	USPAT; EPO; JPO	2004/05/28 11:50
4	6	("5285888" "5287616" "5305518" "5400497" "5541834" "5544411").PN.	USPAT	2004/05/28 12:05
5	9	mounting with component and (recogni\$4 camera) with (nozzle suction) same intermittent with (rotat\$3 rotary)	USPAT; EPO; JPO	2004/05/28 13:23
12	41	mounting with component and (recogni\$4 camera) with (nozzle suction) and intermittent with (rotat\$3 rotary)	USPAT; EPO; JPO	2004/05/28 16:50
15	8	5115559.URPN.	USPAT	2004/05/28 13:31
23	0	mounting with component and (recogni\$4 camera) with (nozzle suction) and intermittent with (rotat\$3 rotary) and lower near speed	USPAT; EPO; JPO	2004/05/28 16:50
24	5	mounting with component and (recogni\$4 camera) with (nozzle suction) and lower near speed	USPAT; EPO; JPO	2004/05/28 16:53
25	133	mounting with component and (recogni\$4 camera) and (rotat\$3 rotary) with (slow \$lower) with speed	USPAT; EPO; JPO	2004/05/28 16:56
26	60	(mounting with component and (recogni\$4 camera) and (rotat\$3 rotary) with (slow \$lower) with speed) and (substrate board)	USPAT; EPO; JPO	2004/05/28 16:56
-	34	component adj mounting.ti. and kanji.in.	USPAT; US-PGPUB; EPO; JPO	2004/02/24 17:33
-	15	("4202092" "4459743" "4480780" "4573262" "4624050" "4631812" "4881319" "5040291" "5115559" "5191702" "5410801" "5541834" "5778524" "5778525" "5806174").PN.	USPAT	2004/02/24 17:58
-	1	5002448.PN.	USPAT; EPO; JPO	2004/05/26 17:47
-	1	5743001.PN.	USPAT; EPO; JPO	2004/05/26 17:47
-	1	5711065.PN.	USPAT; EPO; JPO	2004/05/26 17:48
-	1	5740604.PN.	USPAT; EPO; JPO	2004/05/26 17:48
-	1	5743005.PN.	USPAT; EPO; JPO	2004/05/26 17:53
-	29	component with mounting and supply and head same nozzle same (recognition camera imag\$3) same rotat\$3 and intermittent	USPAT; EPO; JPO	2004/05/26 17:57